

# Palm grip B1



The palm grip B1 has different equipment options for many requirements. It is compatible with our multi-axis controller or mounted on hydraulic drives. The palm grip has a highly flexible cable (4 respectively 8x0,25mm<sup>2</sup>, 450mm long). The mounting piece can be supplied with a tapped hole M10 (standard) or M8.

## Technical data

|                       |                                |
|-----------------------|--------------------------------|
| Operating temperature | -40°C to +60°C                 |
| Degree of protection  | IP54                           |
| Contact complement    | 3A 24V DC13 (*1 1,5A 24V DC13) |



|   | B1 | Example<br>- 2D | W | - X |
|---|----|-----------------|---|-----|
| <b>Basic unit</b>   |    |                 |   |     |
| B1 Palm grip  |    |                 |   |     |
| <b>Digital actuating element</b>  |    |                 |   |     |
| D Push button top   |    |                 |   |     |
| D Push button side *1   |    |                 |   |     |
| W Rocker switch top T-0-T   |    |                 |   |     |
| W Rocker switch top R-0-T   |    |                 |   |     |
| W Rocker switch top R-0-R   |    |                 |   |     |
| T Push button top with mechanical operation<br><i>(Only possible with multi-axis controller or single-axis controller!)</i> |    |                 |   |     |
| K Lever switch  |    |                 |   |     |
| KT Lever switch mechanical operation<br><i>(Only possible with multi-axis controller or single-axis controller!)</i>        |    |                 |   |     |
| <b>Special model</b>  |    |                 |   |     |
| X Special / customer specified  |    |                 |   |     |

