Crane control unit KST 30 swiveling



The KST 30 is an ergonomically designed swiveling crane control chair which provides a high degree of comfort. The inner consoles, mounted to the driver's seat, swing with the seat. The consoles can be positioned to perfectly match any person by means of length, height and inclination adjustment. For console version 1 the whole control unit can be expanded by additional fixed outer consoles. The standard version includes:

Inner consoles:

The plastic consoles can be height-adjusted to match joysticks of any size. In addition consoles can be equipped with custom command and indicating devices.

Outer consoles:

The outer metal consoles feature foldable top covers, including mechanical fixation to keep cover in open position.

Internal terminal strips can easily be accessed be removeable side covers. Command and indicating devices can be added based on customer's choice. Also special sizes and shapes of outer consoles are available on request.

Driver's seat:

The comfortable driver's seat KFS11 is equipped with a spring loaded hydraulic vibration absorption system, including weight adjustment, air-permeable textile cover, arm rests and head rest.

Cross-member with swivel base:

The cover of the sheet steel cross-member including the driver's seat is forward foldable. Thereby all wirings, terminals and bushings are easily accessible during commissioning and maintenance. Swivel base has zero-tolerance bearings and rotation can be locked in

Swivel base has zero-tolerance bearings and rotation can be locked in 3° steps.

Surface treatment:

Base coat and textured varnish

Standard colour RAL 7035 light grey in combination with RAL 7016 anthracite



Industrial Controllers

		KST 311	-3	-M1	-F1	-LK	1	KFS 11	/	V85	/	V85	/	KL	/
Basic un	hit														
KST 301	With inner equipment boxes version 1														
KST 311	With inner eqiupment boxes version 1 and outside eqiupment boxes 160mm wide														
KST 331	With inner eqiupment boxes version 1 and outside eqiupment boxes 270mm wide														
KST 341	With inner eqiupment boxes version 1 and outside eqiupment boxes 320mm wide														
	Special equipment boxes form on request!														
D															
Base un							-								
2	Swiveling 180° left, 90° right with detent			-			-								
3	Electric swiveling 180° left, 90° right Non swiveling						-								
Attachm	nents														
M1	Monitor mounting with monitor housing														
M2	Monitor mounting with monitor mounting brac	ket													
M3	Monitor mounting without monitor housing/ -r	mounting b	racket												
F1	Footrest version 1														
LK	Plate for horizontal manual adjustment for con	ntrol units	+/- 250)mm											
.															
Driver so															
KFS 9*	(Included in the delivery!)														
VEC 10*															
KFS 10* KFS 12*															

Technical details may vary based on configuration or application! Technical data subject to change without notice!

Crane control unit

KST 30 swiveling




		KST 311	-3	-M1	-F1	-LK	/	KFS 11	/	V85	/	V85	/	KL	/	х
Moun	ting for equipment boxes												-			
V	Multi-axis controller (see page 1)												_			
S	Single-axis controller (see page 86)															
D	Double-handle controller (see page 63)															
N	Control-switch (see page 124)															
	More command and indicating devices (see pa	age 188)														
Wirin	9															
KL	Without wiring, but terminal block built in eac	h terminal														
KLV	LV On terminal block 4mm ² with single wire 1mm ² each terminal															
KLV	V On SPS (SPS provision) with single wire 1mm ² each terminal															
KLVA	External wiring single wire highly flexible 1,5	mm² 5m la	ong ea	ich tern	ninal											
	Additional-/ reduction price per meter															
Specia	al model															
Х	Special / customer specified															

X Special painted

3







Floor mou	inting
Ø1	4
3300	cable inlet Ø100
	<u>/</u> ,

adjustable								
Туре	Dim. A	Dim. B	Dim. C					
KST 301	-	-	500					
KST 311	160	1110	610					
KST 331	270	1330	710					
KST 341	320	1430	755					

* adjustable

Technical details may vary based on configuration or application! Technical data subject to change without notice!

3