

# Crane control unit

## KST 85



The KST 85 is an ergonomically designed swiveling crane control chair which provides a high degree of comfort.

### Equipment boxes:

The sheet steel equipment boxes are vertically and horizontally adjustable. The arrangement of the joysticks, indicators and control devices is customised according to customer specifications. Cabling is carried out through a cross-member in the traverse.

(Terminal block)

Special boxes available upon request.

### Driver seat:

The comfortable spring mounted seat KFS 85 with roller-bearing swivel systems.

### Heating console:

Cover with 2 steps heating (2x2kW 400V AC) with integrated ventilator. The cover of the heating cover can be tilted forward to reach the terminal block of the heating and cable execution.

### Surface treatment:

Base coat and textured varnish  
Standard colour RAL 9011 black




Example

KST 85   - M1   /   KFS 82   /   V64   /   V64.1   /   KL   /   X

	KST 85	- M1	/	KFS 82	/	V64	/	V64.1	/	KL	/	X
<b>Basic unit</b>												
KST 85    With heating in the apron												
KST 87    With apron without heating												
<b>Attachments</b>												
M1        Monitor mounting with monitor housing												
M2        Monitor mounting with monitor mounting bracket												
M3        Monitor mounting without monitor housing/-mounting bracket												
<b>Driver seat</b>												
KFS 82* <i>(Included in the delivery!)</i>												
<b>Mounting for equipment boxes</b>												
V...       Multi-axis controller <i>(see page 1)</i>												
S...       Single-axis controller <i>(see page 86)</i>												
D...       Double-handle controller <i>(see page 63)</i>												
N...       Control-switch <i>(see page 124)</i>												
.... <i>More command and indicating devices (see page 188)</i>												
<b>Wiring</b>												
KL        Without wiring, but with terminal block built each terminal												
KLV      On terminal block 4mm <sup>2</sup> with single wire 1mm <sup>2</sup> each terminal												
KLV      On SPS (SPS provision) with single wire 1mm <sup>2</sup> each terminal												
KLVA    External wiring single wire highly flexible 1,5mm 5m long each terminal												
<b>Special model</b>												
X         Special / customer specified												
X <sup>1</sup> Special painted												
<b>Option</b>												
Radio remote control system												

Technical details may vary based on configuration or application! Technical data subject to change without notice!



\* adjustable